

SPECIFICATION SHEETS



PRODUCT NAME:	UL Level 2 - Bullet Resistant Glass
PRODUCT CODE:	BR-155
PERFORMANCE TESTING:	Ballistic: UL Standard 752 - Level 2 – UL Listed – File BP844 .357 Magnum Jacketed Lead Soft Point No Spall, No Penetration
CONSTRUCTION:	Product construction is proprietary.
THICKNESS:	1.812" Nominal
THICKNESS TOLERANCE:	1.691" / 1.935"
WEIGHT:	22.51 Lbs. / Square Foot
SIZE:	60" x 96" Maximum 12" x 12" Minimum
OPTIONS:	Tinted glass, translucent interlayers, transparent mirror, Low Iron glass
TECHNICAL DATA:	U-Value .75 Shading Co-efficient .64 Light Transmission .74
APPLICABLE STANDARDS:	ANSI Z97.1 CPSC 16 CFR 1201 (Category I and II) ASTM C 1036 ASTM C 1172
SINGLE RESPONSIBILITY:	Global Security Glazing products are covered by our Single Responsibility [®] Program that ensures one firm has handled and is accountable for all phases of manufacturing.
INSTALLATION:	Glazing must be installed in a UL Level 2 Bullet Resistant frame system. Holes must be covered with a UL listed device. All glass should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel. Recommended Clearance: Face: 1/8" per side Edge: 3/8" Bite: 1"