## **SPECIFICATION SHEETS**



PRODUCT NAME:	Lexgard™ MP750
PRODUCT CODE:	MP750
PERFORMANCE TESTING:	Ballistic: UL 752- Level 1 – UL Listed – File BP844 9 mm Full Metal Copper Jacket with Lead Core No Spall, No Penetration
CONSTRUCTION:	This product is laminated polycarbonate and contains exposed polycarbonate surfaces with abrasion resistant coatings on both sides.
THICKNESS:	.766" Nominal
THICKNESS TOLERANCE:	.690" / .842"
WEIGHT:	4.76 Lbs. / Square Foot
SIZE:	72" x 96" Maximum 12" x 12" Minimum
OPTIONS:	Bronze, gray, green tint
TECHNICAL DATA:	U-Value .67 Solar Heat Gain Co-efficient .78 Light Transmission .80
SINGLE RESPONSIBILITY:	Global Security Glazing products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing
INSTALLATION:	Glazing must be installed in a UL Level 1 Bullet Resistant frame system. Holes must be covered with a UL listed device. All glazing should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel.
	Recommended Clearance: Face: 1/8" per side Edge: 3/8" Bite: 1"