DECORATIVE, SPECIALTY, & BENT GLASS



Formerly Dlubak Specialty Glass



Isoclima offers specialty architectural glazing solutions, including decorative, specialty, and bent glass options, enhancing project design while prioritizing safety.

APPLICATIONS

- Exterior Vision
- Spandrel Areas
- Insulating Glass Units (IGUs)
- Skylights
- Solariums
- Covered Walkways
- Interior Walls
- Office Partitions
- Handrails
- Staircases
- Balconies
- Revolving Doors
- Shower Doors

Maximum Size Tempered Girth/Arch - 98.4" [2500mm] Height - 137.8" [3500mm]

Minimum Size Tempered 23.6" [600mm] Girth/Arch x 19.7" [500mm] High

No Minimum Size Annealed


AVAILABLE FABRICATION OPTIONS

- Laminated with polyvinyl butyral (PVB) or SentryGlas™
- Insulated with or without certain low-emissivity glass
- Available in clear, low-iron and tinted glass
- Frit silk-screen patterns
- Cutting patterns
- Seamed edges are standard, polished or ground edges are available upon request.



GAGE	ANNEALED	TEMPERED
1/8" [3mm]	Х	
3/16" [5mm]	X	Minimum Radius 39.4" [1000mm]
1/4" [6mm]	Х	Minimum Radius 39.4" [1000mm]
5/16" [8mm]	Х	Minimum Radius 47.2" [1200mm]
3/8" [10mm]	Х	Minimum Radius 47.2" [1200mm]
1/2" [12mm]	Х	Minimum Radius 59.1" [1500mm]
5/8" [16mm]	х	Minimum Radius 78.7" [2000mm]
3/4" [19mm]		Minimum Radius 78.7" [2000mm]





Maximum and minimum sizes depend on composition, glass plies, size, glass ply thickness and bend detail.

DECORATIVE, SPECIALTY, & BENT GLASS



Formerly Dlubak Specialty Glass









