

PRODUCT NAME:	1 ¼" LEXGARD™ RS1250
PRODUCT CODE:	RS 1250
PERFORMANCE TESTING:	Ballistic: UL 752- Level 6 – UL Listed – File BP844 .9 mm submachine gun, Supplementary Shotgun (12-gauge rifled lead slug and lead buckshot) No Spall, No Penetration
THICKNESS:	Nominal (1.28")
THICKNESS TOLERANCE:	1.15" /1.41"
WEIGHT:	7.73 Lbs. / Square Foot
SIZE:	72" x 96" Maximum 12" x 12" Minimum for UL Ballistic Rating
OPTIONS:	Bronze, gray, green tint
TECHNICAL DATA:	U-Value- 56 Shading Co-efficient- .98 Light Transmission- .78 Solar Heat Gain Co-efficient- .84 ANSI Z97.1 CPSC 16 CFR 1201 (Category I and II) ASTM C 1349
APPLICABLE STANDARDS:	Global Security Glazing products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing.
SINGLE RESPONSIBILITY:	When used for ballistic protection, glazing should be installed in a UL Level 3 Bullet Resistant frame system. Holes should be covered with a UL listed device. All glazing should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel.
INSTALLATION:	Recommended Clearance: Face: 1/8" per side Edge: 1/4" Bite: 1"

DB013A 27 March 2023